

X15 32.768 kHz SURFACE-MOUNT CRYSTAL

FEATURES

- Smallest industry package size for 32.768 kHz
- Extended temperature -40/+85°C for industrial applications
- Applications : Wireless applications , Commercial and Industrial applications

1.6 x 1.0 x 0.5 mm



Item	Symbol	Specification
Nominal Frequency	Fo	32.768 kHz
Cut		XY-cut
Operating temperature Range	To	-40° to +85°C
Frequency Tolerance at 25°C	Δf/F	± 20ppm standard (see options)
Temperature coefficient	β	-0.040 ppm/°C ² max
Load Capacitance (CL)	CL	12.5 pF standard (see options)
Equivalent Series Resistance	ESR	90 kΩ max.
Insulation Resistance	Ri	500 MΩ min. (at 100Vdc)
Drive Level	DL	0.5 μW max.
Aging	Δf/F	±3ppm max (at 25°C, first year)
Packing Unit		3000pcs / reel
Soldering Condition		260°C, 10 sec x2 max

OPTIONS & ORDERING INFORMATION

X15- — —	32.768 kHz
	Freq. Tolerance	Load Capacitance	
	10 = ±10 ppm	12.5 = 12.5 pF	
	20 = ±20 ppm	9 = 9.0 pF	
	30 = ±30 ppm		
	50 = ±50 ppm		

OUTLINE DIMENSIONS

